

Feature

- * Color mixing system: integrated powerful beam and dyeing functions.
- * Controllable, uniform RGBW color mixing system and rainbow effect.
- * CTO color temperature adjustment (2500K-8000K).
- * Focusing: linear focusing system, 0~100% smooth dimming.
- * Scanning range: X-axis 540~630°/2.7S, Y-axis 210°/1.5S, accurate scanning and positioning.
- * Outstanding strobe effect with variable speed.
- * Compact structure and small size.
- * Fast running speed, no noise in operation, no flicker under HD camera.

Specification

ModelTL-SL157Input voltageAC110V-240V 50/60Hz, 350WLight source7 × 40W RGBW LED lamp beadLens outer36 × 0.5W RGB 3IN1 LEDBeam angle8°-64°Average lifespan50000HControl modeDMX512 protocol, support RDM protocol and program online update function, support Art-net Ethernet data interface, DMX wireless function is optionalChannel15 channelsFixture materialHigh temperature plastic + molded alloy materialProtection classIp30Fixture size (L×W×H)329×227×406mmPackage size (L×W×H)505×420×290mmGross weight11.6kgNet weight9.3kg	<u>-</u>	
Light source 7 × 40W RGBW LED lamp bead Lens outer 36 × 0.5W RGB 3IN1 LED Beam angle 8°~64° Average lifespan 50000H Control mode DMX512 protocol, support RDM protocol and program online update function, support Art-net Ethernet data interface, DMX wireless function is optional Channel 15 channels Fixture material High temperature plastic + molded alloy material Protection class Ip30 Fixture size (L×W×H) 329×227×406mm Package size (L×W×H) 505×420×290mm Gross weight 11.6kg	Model	TL-SL157
Lens outer 36 × 0.5W RGB 3IN1 LED Beam angle 8°~64° Average lifespan 50000H Control mode DMX512 protocol, support RDM protocol and program online update function, support Art-net Ethernet data interface, DMX wireless function is optional Channel 15 channels Fixture material High temperature plastic + molded alloy material Protection class Ip30 Fixture size (L×W×H) 329×227×406mm Package size (L×W×H) 505×420×290mm Gross weight 11.6kg	Input voltage	AC110V-240V 50/60Hz, 350W
Beam angle 8°~64° Average lifespan 50000H Control mode DMX512 protocol, support RDM protocol and program online update function, support Art-net Ethernet data interface, DMX wireless function is optional Channel 15 channels Fixture material High temperature plastic + molded alloy material Protection class Ip30 Fixture size (L×W×H) 329×227×406mm Package size (L×W×H) 505×420×290mm Gross weight 11.6kg	Light source	7 × 40W RGBW LED lamp bead
Average lifespan Control mode DMX512 protocol, support RDM protocol and program online update function, support Art-net Ethernet data interface, DMX wireless function is optional Channel 15 channels Fixture material High temperature plastic + molded alloy material Protection class Ip30 Fixture size (L×W×H) 329×227×406mm Package size (L×W×H) 505×420×290mm Gross weight 11.6kg	Lens outer	36 × 0.5W RGB 3IN1 LED
Control mode DMX512 protocol, support RDM protocol and program online update function, support Art-net Ethernet data interface, DMX wireless function is optional 15 channels Fixture material Protection class Ip30 Fixture size (L×W×H) 329×227×406mm Package size (L×W×H) 505×420×290mm Gross weight 11.6kg	Beam angle	8°~64°
support Art-net Ethernet data interface, DMX wireless function is optional Channel 15 channels Fixture material High temperature plastic + molded alloy material Protection class Ip30 Fixture size (L×W×H) 329×227×406mm Package size (L×W×H) 505×420×290mm Gross weight 11.6kg	Average lifespan	50000H
Channel 15 channels Fixture material High temperature plastic + molded alloy material Protection class Ip30 Fixture size (L×W×H) 329×227×406mm Package size (L×W×H) 505×420×290mm Gross weight 11.6kg	Control mode	DMX512 protocol, support RDM protocol and program online update function,
Fixture material High temperature plastic + molded alloy material Protection class Ip30 Fixture size (L×W×H) 329×227×406mm Package size (L×W×H) 505×420×290mm Gross weight 11.6kg		support Art-net Ethernet data interface, DMX wireless function is optional
Protection class lp30 Fixture size (L×W×H) 329×227×406mm Package size (L×W×H) 505×420×290mm Gross weight 11.6kg	Channel	15 channels
Fixture size (L×W×H) 329×227×406mm Package size (L×W×H) 505×420×290mm Gross weight 11.6kg	Fixture material	High temperature plastic + molded alloy material
Package size (L×W×H) 505×420×290mm Gross weight 11.6kg	Protection class	lp30
Gross weight 11.6kg	Fixture size (L×W×H)	329×227×406mm
•	Package size (L×W×H)	505×420×290mm
Net weight 9.3kg	Gross weight	11.6kg
	Net weight	9.3kg