



LED Flood Light

TL-LH3203



Description

Application: Building facades, squares, leisure sports fields, stages, billboards, rockery, building exterior lighting, landscape lighting, signs and indicative lighting, entertainment venues and stage lighting, bridges, etc.

Features

- *Smooth appearance curve, stylish and beautiful appearance. Cavity structure and independent heat dissipation are adopted to fully guarantee the stability and long lifespan of the LED.
- *High-conductivity aluminum radiator, ventilation and convection design, smaller fixture and the larger power. SUS304 stainless steel screw bracket is equipped with a dial, with gear locking function.
- *Glue-free waterproof design, protection level IP65.
- *The fixture is made of high-strength die-cast aluminum, and the surface is treated with fluorocarbon spraying. The lampshade is made of high-strength tempered glass, which is resistant to impact and friction.
- *Good electromagnetic compatibility and no electromagnetic interference to the surrounding environment.

Specifications

| | |
|------------------------------|--|
| Model | TL-LH3203 |
| Input voltage/power | DC24V/50Hz/10W |
| Number of LEDs/light sources | CREE/4PCS |
| Beam angle | 8° |
| Color temperature | 3000K (1900, 2100, 4000, 5700K optional) |
| Installation method | Fixed |
| IP rating | IP65 |
| Product size (L×W×H) | 85×85×92mm |
| Packing size (L×W×H) | 670×280×175mm |
| Gross weight | 10KG (10PCS/box) |
| Net weight | 0.8KG |
| Certification | CE/ROHS |