



Moving Head Beam Light

TL-SL102



Feature:

- * Optics: high-precision glass optical lens (6-layer coating film), and multi-level optical lens group electronic focusing.
- * Color panel: 13 color plate + 1 blank, bidirectional rainbow effect, adjustable speed, and arbitrary positioning function.
- * Fixed pattern panel: 13 fixed pattern plate + 1 blank, pattern dithering, one-way flow effect, adjustable speed, and arbitrary positioning function.
- * Prism: one 16-sided prism + one 8-sided prism, and one double prism (8-sided prism + 16-sided prism).
- * Strobe: double-chip strobe 0.5-14 times/sec, support synchronous, asynchronous, random stroboscopic mode, and adjustable speed.
- * Atomization: 1 independent atomization effect with soft and natural light spot.
- * Scan range: X-axis 540°/2.5 S, Y-axis 270°/1.5 S; resolution: 8Bit/16Bit.
- * Display interface: a 2.8-inch widescreen LCD interface in Chinese and English.
- * Positioning technology: magnetolectric positioning system uses magnetic devices to replace the traditional Hall positioning system, getting higher accuracy and more reliable performance.

Specifications:

Model	TL-SL102
Input voltage	AC110V-240V 50/60Hz, 470W
Ballast	Electronic ballast
Light source	17R/YODN MSD 350
Average lifespan	2000H
Color temperature	8500K
Beam angle	Parallel light 0-2°, fog light 8°
Control mode	DMX512 (ART-NET/RDM/DMX wireless, optional)
Channel	18 channels
Fixture material	High temperature resistant plastic + molded alloy material
Protection level	IP20
Fixture size (L×W×H)	360×260×555mm
Package size (L×W×H)	440×440×555mm
Gross weight	20kg
Net weight	17.5kg