



# Par Light

## TL-SL207



### Feature:

- \* Strobe: independent electronic strobe 1-25Hz; support random strobe, pulse strobe, synchronous and asynchronous strobe, single color and mixed color temperature strobe.
- \* Color mixing: RGBW (red, green, blue and white) linear color mixing, 16.7 million colors (0-100% saturation adjustment), and built-in macro function.
- \* Electronic dimming: 0-100% independent electronic linear dimming, lifelike and flicker-free camera video, the master-slave self-propelled automatic synchronization function, and the console normally controls the self-propelled permanent synchronization.
- \* LCD menu: invoke various scenes; built-in programs can be directly invoked and executed.
- \* Fixture connection: three-core signal line IN/OUT and power line IN/OUT.
- \* Cast aluminum housing, high luminous efficiency, uniform light mixing, and stable performance; equipped with a 1m hand-in-hand power line and signal line of 1 in and 1 out.
- \* Voice control sensitivity: 65-130dB.

### Specifications:

|                      |   |
|----------------------|---|
| Model                | TL-SL207  |
| Input voltage        | AC 110-240V 50/60Hz, 360W   |
| Light source         | 120×3W LED(R30G30B30W30)  |
| Average lifespan     | 50000H  |
| Color temperature    | 3200K~7200K linear adjustment   |
| Beam angle           | 25°(15°, 45° optional)  |
| Control mode         | Multiple voice control, DMX512, built-in self-propelled program, master-slave online mode |
| Channel              | 4/8 channels  |
| Fixture material     | Cast aluminum housing   |
| Protection level     | Fireproof V-1, protection IP20  |
| Fixture size (L×W×H) | 325×260×290mm   |
| Package size (L×W×H) | 310×310×420mm   |
| Gross weight         | 8kg   |
| Net weight           | 7.5kg   |