



## LED Flood Light

### TL-SL294



#### Descriptions

\* Strobe: fast electronic strobe 0-20Hz.

\* Color mixing: RGBW (red, green, blue and white) linear color mixing, 16.7 million colors (0-100% saturation adjustment), and built-in macro function.

\* Electronic dimming: 0-100% independent electronic linear dimming, lifelike and flicker-free camera video, the master-slave self-propelled automatic synchronization function, and the console normally controls the self-propelled permanent synchronization.

\* Display menu: 0802LCD operation panel, support the invocation of various scenes; built-in programs can be directly invoked and executed.

\* Temperature control: with intelligent temperature protection function to ensure the LED lifespan.

<b>Model</b>	TL-SL294
<b>Input voltage</b>	AC 110-240V 50/60Hz, 240W
<b>Light source</b>	18×12W LED(4IN1)
<b>Average lifespan</b>	50000H
<b>Beam angle</b>	15°
<b>Fixture connection</b>	Three-core signal line IN/OUT and power line IN/OUT
<b>Control mode</b>	DMX512, built-in self-propelled program, master-slave online mode, support RDM and program online update
<b>Channel</b>	3/4/7 channels
<b>Fixture material</b>	Aluminum alloy die-casting structure
<b>Protection level</b>	Fireproof V-1, protection IP30
<b>Fixture size (L×W×H)</b>	269×177×366mm
<b>Net weight</b>	8.0kg
<b>Working temperature</b>	-20 C~40 C