

Description

LED underground light is widely used for outdoor lighting in squares, parks, leisure places, etc. It is also used for night lighting in park gardens, lawns, courtyards, flower beds, pedestrian streets, waterfalls, fountains and so on.

Feature

- * Reasonable heat dissipation design enables the heat of the LED to be quickly conducted through the light structure and ensures its luminous efficiency and service lifespan;
- * The flat glass and stainless steel surface cover are perfectly seamless to avoid dust deposits;

- * The low-gradient surface cover allows pedestrians to walk without obstacles and prevents them from falling;
- * Aviation aluminum extrusion fixture, surface electrostatic spraying treatment, wire-drawing stainless steel surface cover, and die-casting aluminum rear cover;
- * Ultra-white tempered glass, with seismic and impact protection grade of IK10, and strong load-bearing capacity.

Specification

Model	TL-LH6125	TL-LH6126	TL-LH6127
Input voltage/power	DC24V/3W	DC24V/6W	DC24V/12W
Number of LED lamp bead/ light source	Philips/3PCS	Philips/6PCS	Philips/12PCS
Beam angle	15° (30, 45, 60° optional)		
Color temperature	RGB		
Control method	1		
Installation method	Embedded		
IP level	lp67		
Fixture size (L×W×H)	D100*106mm	D130*96mm	D180*122mm
Temperature	-20~+50°C		