



Description

With the continuous development of urbanization, LED linear lights are used more and more in urban lighting projects. They are very practical and can be freely matched to highlight the outline of buildings, or to make digital screen effects.

Features

- * Unique structure, simple and beautiful appearance, waterproof design with full sealant potting, and protection level of IP65;
- * 6063 aluminum alloy fixture, SUS304 stainless steel screw, multiple installation methods, surface electrostatic spraying paint, strong corrosion resistance, making it suitable for harsh outdoor environments;
- * It has the excellent optical performance, and the external anti-UV PC cover can effectively improve the uniformity of light mixing effects;
- * The integration of monochromatic/RGB/RGBW supports DMX512 control system; concise wiring makes the fixture installation and maintenance more convenient;
- * Electronic constant current program design ensures more stable performance; the seamless structure design is adopted.

Specifications

•	
Model	TL-LH2407
Input voltage/power	DC24V/50Hz/12W
Number of LED lamp bead/light source	Epistar 5050/48PCS
Beam angle	120°
Color temperature	RGBW (W=5700K)
Control method	DMX512/8 bands
Installation method	Fixed (fastener is optional)
IP level	IP65
Fixture size (L×W×H)	1000×28×40mm
Net weight	0.9KG
Certificate	CE/ROHS